




Position	Qty.	Description	Single Price
	1	<p>25 SQF-7</p>  <p>Note! Product picture may differ from actual product</p> <p>Product No.: 95027353</p> <p>The 4" SQF centrifugal pump is for low heads and large flows.</p> <p>Features and benefits:</p> <ul style="list-style-type: none"> -Dry-running protection -High efficiency permanent-magnet motor (PM motor) -Over- and undervoltage protection -Overload protection -Maximum Power Point Tracking (MPPT) -Wide voltage range <p>Liquid:</p> <p>Pumped liquid: Water Maximum liquid temperature: 40 °C Liquid temp: 20 °C Density: 998.2 kg/m³</p> <p>Technical:</p> <p>Approvals on motor nameplate: CE</p> <p>Materials:</p> <p>Pump: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Installation:</p> <p>Maximum ambient pressure: 15 bar Pump outlet: 1 1/2 NPT" Minimum borehole diameter: 102 mm</p> <p>Electrical data:</p> <p>Motor type: MSF3 Power input - P1: 1.4 kW Rated voltage ac: 1 x 90-240 V Rated voltage dc: 30-300 V Start. method: direct-on-line</p>	On request

Position	Qty.	Description	Single Price
		Rated current: 8.4 A Power factor: 1,0 Rated speed: 500-3600 rpm Enclosure class (IEC 34-5): 68 Insulation class (IEC 85): F Length of cable: 2 m Others: Net weight: 8.8 kg Gross weight: 10.3 kg Shipping volume: 0.028 m3	

95027353 25 SQF-7 50 Hz

