



samlexamerica

250W

DC-AC Inverter
Modified Sine Wave

Model
SAM-250-12
 12 VDC - 115 VAC

Design Features

- USB charging port: 5 VDC, 500 mA
- Compact design with cigar lighter plug included
- Load controlled cooling fan
- Low battery input alarm
- Universal protection circuit: thermal, battery, overload, short circuit, earth fault
- Soft start technology
- Cool surface technology
- Power save mode
- Low interference technology



2 YEAR WARRANTY

MODEL NO. SAM-250-12

INPUT	BATTERY SYSTEM VOLTAGE	12 VDC
	NOMINAL INPUT VOLTAGE	12.5 VDC
	INPUT VOLTAGE RANGE	10.5 VDC to 16 VDC
	INPUT CURRENT AT CONTINUOUS POWER	22.3 A to 24.2 A
	INPUT CURRENT AT NO LOAD	0.2 A to 0.3 A
OUTPUT	OUTPUT VOLTAGE WAVE FORM	Modified Sine Wave
	OUTPUT VOLTAGE	115 VAC
	OUTPUT VOLTAGE REGULATION	+5% / - 2%
	OUTPUT FREQUENCY	60 Hz +/- 5%
	OUTPUT POWER, CONTINUOUS (RESISTIVE LOAD)	250 W
	OUTPUT POWER, SURGE (< 1 SEC, RESISTIVE LOAD)	500 W
	PEAK EFFICIENCY (AT 50% OF CONTINUOUS POWER)	90%
PROTECTIONS	USB CHARGING PORT	5 VDC, 500 mA
	LOW INPUT VOLTAGE ALARM	Yes (10.8 +/- 0.3 VDC)
	LOW INPUT VOLTAGE SHUTDOWN	10.5 +/- 0.3 VDC
	HIGH INPUT VOLTAGE SHUTDOWN	Yes. (> 15.5 VDC)
	OVERLOAD SHUT DOWN	Yes (Latches in shutdown condition. Manual reset by switching off and switching on the On / Off Switch)
	OVER TEMPERATURE SHUTDOWN	Yes (Auto reset)
	COOLING FAN, LOAD CONTROLLED, ON AT	8 to 12 W
CONNECTIONS	LEAKAGE PROTECTION	Yes (Shutdown)
	INPUT FUSE, 32 V	30 A
	INPUT CONNECTION	Nut and Bolt
REMOTE CONTROL PORT	OUTPUT CONNECTION - NO OF NEMA5-15R RECEPTACLES	1
		No
GENERAL	OPERATING TEMPERATURE RANGE	0 to 25 C at 100% loading; 26 C to 35 C at 80% loading
	OPERATING HUMIDITY	< 80%
	NEUTRAL TO CHASSIS BONDING	No. Neutral is floating
	DIMENSIONS, MM	150 x 114.4 x 46
	DIMENSIONS, IN	5.9 x 4.5 x 1.8
	WEIGHT, KG	.42
	WEIGHT, LB	.92

NOTE: Specifications are subject to change without notice